

WHAT IS CLAIMED IS

ORIGINAL SUBMITTED

- 20881
1. A reforming method comprising two or more  
5 reforming rooms (6) connected in series, in which a gas  
mixture (2) comprising a fuel, water and air is supplied to  
one end thereof and a reformed gas (4) containing hydrogen  
is discharged from the other end thereof, wherein  
a first catalyst (8a) that catalyzes a partial  
10 oxidation reaction in an oxygen environment is loaded into  
the upstream end of each of the reforming rooms, and a  
second catalyst (8b) for the reforming reaction is charged  
into the downstream portion thereof, and  
the gas mixture is supplied directly to one end of  
15 each reforming room, and the reformed gas is discharged  
from the other end of the furthest downstream reforming  
room.
2. The reforming method specified in Claim 1, wherein  
the same catalyst that can catalyze both the partial  
20 oxidation and reforming reactions is used as the first and  
second catalysts (8a, 8b).
3. The reforming method specified in Claims 1 or 2,  
comprising a reforming tube (10) composed of two or more of  
the reforming rooms (6) connected in series, and a reformer  
25 housing (12) that encases the reforming tube, wherein  
a high-temperature heating gas (16) is introduced  
into the space (14) formed between the reforming tubes and  
the reformer housing, and after the first catalyst (8a) and

the second catalyst (8b) have been heated up from outside the reforming room, the gas mixture (2) is supplied to each reforming room to undergo reforming.

4. The reforming method specified in Claims 1, 2 or 3, wherein the high-temperature heating gas (16) is supplied directly to one end of each of the reforming rooms (6) and is discharged from the other end of the furthest downstream reforming rooms, and after the first and second catalyst (8a, 8b) are heated up from inside the reforming rooms, the gas mixture (2) is supplied to each reforming room to undergo reforming.

5. A reforming apparatus comprising  
a mixed gas feed tube (18) that supplies a gas mixture (2) composed of a fuel, water and air, and  
a reforming tube (10) that converts the gas mixture into a reformed gas (4) containing hydrogen, wherein the reforming tube comprises two or more reforming rooms (6) connected together in series, in which the gas mixture (2) is supplied to one end and the reformed gas (4) is discharged from the other end thereof,

- each of the reforming rooms is filled with a first catalyst (8a) that catalyzes a partial oxidation reaction in an oxygen environment in the upstream portion thereof, and with a second catalyst (8b) for reforming in the downstream portion, and

gas feed means (20) are provided on the mixed gas feed tube, that directly supply the gas mixture to each reforming room.

5/18/81

6. The reforming apparatus specified in Claim 5,  
in  
the gas feed means (20) comprises an outer cylinder  
that covers one end of the reforming tube (10) and at  
a part of the side surface thereof, and forms a gap  
around the reforming tube in the peripheral direction  
works as a passage for the gas mixture,  
inlet ports (26) are disposed on the side surface of  
reforming tube and supply the gas mixture to each  
reforming room from the gap, and  
the inlet ports comprise flow control mechanisms  
(28b) or flow regulate means (32a, 32b) for adjusting  
flow of the gas mixture supplied to each reforming room.

7. The reforming apparatus specified in Claim 5,  
in the gas feed means (20) comprises a hollow  
distribution tube (34) for passing the gas mixture (2)  
through the interior of at least one of the reforming rooms,  
one end thereof in the downstream direction of the  
reforming tube (10),  
the penetration tube comprises inlet ports (36a, 36b)  
to supply the gas mixture individually to each reforming  
room, and  
the inlet ports comprise flow control mechanisms  
(28b) or flow regulate means (32a, 32b) for adjusting  
flow of the gas mixture introduced into each reforming

5

10

© 2000 by The McGraw-Hill Companies, Inc.

15

20

25

Sub B1

reforming tube (10), and a first heating gas tube (28a) for introducing a high-temperature heating gas (16) into the space (14) formed between the reformer housing and the reforming tube, from the outside.

- 5           9. The reforming apparatus specified in Claims 5, 6, 7 or 8, wherein a second heating gas tube (38b) is connected to the mixed gas feed tube (18), to introduce a high-temperature heating gas (16) from the outside.

10           10. In the reforming apparatus that converts a gas mixture (102) comprising a fuel gas, steam and air, into hydrogen,

          a reforming apparatus comprising a heating unit (104) for evaporating and heating the gas mixture, a distribution tube (108) that distributes the heated gas mixture evenly  
15 to a plurality of branch ports (106) disposed at one end thereof, a reforming unit (114) filled with a reforming catalyst (112) for catalyzing the gas mixture, a manifold (116) comprising the distribution tube on the inside thereof, a CO removal unit (124) filled with a CO removal  
20 catalyst (122) used to remove CO from the gas (118) reformed in the reforming unit, and a casing (126) for housing the reforming unit, the manifold and the CO removal unit, wherein

          the reforming unit comprises a reforming room (132)  
25 composed of a reforming tube (130) of which one end is connected to the branch port and from the other end of which the reformed gas is discharged, or configured by disposing two or more of the reforming tubes parallel to

5  
435

10  
15  
20  
25

5/10/81

each other, and a feedback mechanism (134) for passing the reformed gas around the outer periphery of the reforming tubes and sending the gas to the manifold.

11. The reforming apparatus specified in Claim 10,  
5 wherein the CO removal unit (124) is located opposite or parallel to the reforming unit (114) and communicates with the manifold (16).

*Sub B*

10  
15  
20  
25

12. The reforming apparatus specified in Claims 10 or 11, wherein the feedback mechanism (134) sends the reformed gas (118) to the manifold through a reformed gas passage (136) formed by the space between the reforming tubes (130) located close to each other or between the reforming tubes and the casing (126), in the axial direction of the reforming tubes.

13. The reforming apparatus specified in Claims 10, 11 or 12, wherein the reforming tubes (13) can be freely removed and replaced.

14. The reforming apparatus specified in one of Claims 10 to 13, wherein a fuel trap unit (138) is disposed  
20 between the manifold (116) and the CO removal unit (124), to remove fuel gas from the reformed gas (118).

15. The reforming apparatus specified in one of Claims 10 to 14, wherein the manifold (116) comprises a feed tube (142) for feeding oxygen, air or steam to the  
25 reformed gas (118) sent to the CO removal unit (124).

*Sub B*  
16. The reforming apparatus specified in Claim 15, wherein the CO removal unit (124) comprises one section or two or more sections, and feed tubes (142a, 142b) are

*Sub B*

8681

disposed on the upstream side of each section to supply  
oxygen, air or steam.

SUSAY  
~~REDACTED~~

Add 627

FOUO 20250160